

1. Identification

Product identifier	Presaturated wipes containing 70% Isopropyl alcohol, 30% water	
Other means of identification		
SDS number	7030SCFL	
Product code	CSPS0001A, PSCS0009B, PS-LPP-7030, PS-LPP-7030IR, PSPS0002, PSPS0008, PSPS0034, PSQS0001, PSQT0100, PSWE0002, PSWE0002PFZ, SMPP0007, SW420946, SW420996, SWNW0013, SWPP0003	
Recommended use	Wipe for critical cleaning.	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/Distributor information		
Company name	Contec, Inc.	
Address	525 Locust Grove Spartanburg, SC 29303 USA	
Telephone	1-864-503-8333	
Email	SDS@contecinc.com	
Emergency phone number	Call CHEMTREC day or night USA/Canada: 1.800.424.9300 Mexico: 1.800.681.9531 Outside USA/Canada: +1.703.527.3887	

2. Hazard identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Serious eye damage/eye irritation	Category 2A
Label elements		



Signal word	Danger	
Hazard statement	Highly flammable liquid and vapour. Causes serious eye irritation.	
Precautionary statement		
Prevention	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.	
Response	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. In case of fire: Use appropriate media to extinguish.	
Storage	Store in a well-ventilated place. Keep cool.	
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.	
Supplemental information	Although the product as a whole is in solid format, the product does not meet the OSHA HCS definition of a flammable solid as per Appendix B to 1910.1200 - Physical Hazard Criteria, section B.7.1 and B. 7.2 or Canada's Hazardous Products Regulations Subpart 7.	
Other hazards	None known.	

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Propan-2-ol		67-63-0	70
Other components below reportable levels			30

Composition comments All concentrations are in percent by volume.

4. First-aid measures

Inhalation	Not relevant, due to the form of the product. However: If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison centre or doctor/physician if you feel unwell.
Skin contact	Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Not relevant, due to the form of the product. In case of ingestion: Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Direct contact with eyes causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. In high concentrations, vapours are narcotic and may cause headache, fatigue, dizziness and nausea.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	May burn with invisible flame. Vapours may form explosive mixtures with air. Vapours are heavier than air and may spread near ground to sources of ignition. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed. Carbon oxides. Organic compounds.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Cool containers exposed to flames with water. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Solid containing flammable liquid.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Avoid contact with skin, eyes and clothing. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Avoid release to the environment. The liquid solvent solution is miscible in water. Spills are very unlikely, because the wiper fabric has absorbed the liquid solvent solution. In the event of a spill, contain with an inert absorbent. Collect the wipes with a non sparking tool and absorb or wipe any residual liquids. Put material in suitable container.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

WARNING! Used wipes may catch fire if improperly discarded or stored near ignition sources. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Avoid breathing mist/vapours. Avoid contact with skin, eyes and clothing. Avoid prolonged exposure. Wash thoroughly after handling. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Keep containers closed when not in use. Store away from incompatible materials (see section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Type	Value
Propan-2-ol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value
Propan-2-ol (CAS 67-63-0)	STEL	984 mg/m ³
		400 ppm
	TWA	492 mg/m ³
		200 ppm

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value
Propan-2-ol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value
Propan-2-ol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

Canada. New Brunswick OELs: Threshold Limit Values (TLVs) Based on the 1991 and 1997 ACGIH TLVs and BEIs Publication (New Brunswick Regulation 91-191)

Components	Type	Value
Propan-2-ol (CAS 67-63-0)	STEL	1230 mg/m ³
		500 ppm
	TWA	983 mg/m ³
		400 ppm

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value
Propan-2-ol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Components	Type	Value
Propan-2-ol (CAS 67-63-0)	STEL	1230 mg/m ³
		500 ppm
	TWA	985 mg/m ³
		400 ppm

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)

Components	Type	Value
Propan-2-ol (CAS 67-63-0)	15 minute	400 ppm
	8 hour	200 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Propan-2-ol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*

* - For sampling details, please see the source document.

Exposure guidelines

Follow standard monitoring procedures.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection

Not necessary under normal conditions.

Skin protection

Hand protection

Wear appropriate chemical resistant gloves. Take note of the information given by the manufacturer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
Recommended materials: Polyethylene. Neoprene. Chlorinated polyethylene (or Chlorosulfonated polyethylene). Natural rubber. Polyvinyl chloride (PVC). Nitrile rubber/Nitrile latex - NBR Ethyl vinyl alcohol laminate ("EVAL").
Unsuitable materials: Polyvinyl alcohol (PVA).

Other

Wear suitable protective clothing.

Respiratory protection

Not necessary under normal conditions. If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Selection and use of respiratory protective equipment should be in accordance with CSA Standard Z94.4. Check with respiratory protective equipment suppliers.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state

Liquid.

Form

Wipes saturated with liquid.

Colour

Colourless.

Odour

Alcohol-like.

Odour threshold

Not available.

pH

Property has not been measured. (liquid)

Melting point/freezing point

Property has not been measured. (liquid)

Initial boiling point and boiling range

82 - 89 °C (179.6 - 192.2 °F) (liquid)

Flash point

20.5 °C (68.9 °F) (liquid)

Evaporation rate

Property has not been measured. (liquid)

Flammability (solid, gas)

Wipes will burn if involved in a fire.

Upper/lower flammability or explosive limits

Explosive limit - lower (%)

2 % (liquid)

Explosive limit – upper (%)

12 % (liquid)

Vapour pressure

43 hPa (32 mm Hg) (20 °C (68 °F) (liquid))

Vapour density

Property has not been measured. (liquid)

Relative density	0.872 (20 °C (68 °F) (liquid))
Solubility(ies)	
Solubility (water)	Soluble in water. (liquid)
Partition coefficient (n-octanol/water)	Not applicable to mixtures.
Auto-ignition temperature	399 °C (750.2 °F) (liquid)
Decomposition temperature	Property has not been measured.
Viscosity	Property has not been measured. (liquid)
Other information	
Density	129.28 mg/m ³
Explosive properties	Not explosive.
Kinematic viscosity	Property has not been measured. (liquid)
Oxidising properties	Not oxidising.
Percent volatile	100 % (IPA)

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Aldehydes. Halogenated organics. Halogens. Strong acids. Strong oxidising agents.
Hazardous decomposition products	Combustion may produce: Oxides of carbon and other organic substances.

11. Toxicological information

Information on likely routes of exposure

Inhalation	No inhalation hazard under normal conditions. However: Prolonged inhalation of vapors may be harmful. May cause drowsiness or dizziness. Headache. Nausea, vomiting.
Skin contact	Prolonged skin contact may cause temporary irritation.
Eye contact	Not relevant, due to the form of the product. However: Direct contact: Causes serious eye irritation.
Ingestion	Not relevant, due to the form of the product.

Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. In high concentrations, vapours are narcotic and may cause headache, fatigue, dizziness and nausea.
---	--

Information on toxicological effects

Acute toxicity	Not relevant, due to the form of the product in its manufactured and shipped state.
-----------------------	---

Components	Species	Test Results
Propan-2-ol (CAS 67-63-0)		
Acute		
Dermal		
LD50	Rabbit	12870 mg/kg
Inhalation		
<i>Vapour</i>		
LC50	Rat	72.6 mg/l, 4 hours
Oral		
LD50	Rat	4710 mg/kg
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Not relevant, due to the form of the product. However: Direct contact: Causes serious eye irritation.	

Respiratory or skin sensitisation

Respiratory sensitisation Not a respiratory sensitiser.

Skin sensitisation This product is not expected to cause skin sensitisation.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

ACGIH Carcinogens

Propan-2-ol (CAS 67-63-0) A4 Not classifiable as a human carcinogen.

Canada - Manitoba OELs: carcinogenicity

Propan-2-ol (CAS 67-63-0) Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Propan-2-ol (CAS 67-63-0) 3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified. However: In high concentrations, vapours are narcotic and may cause headache, fatigue and nausea.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Frequent or prolonged contact may defat and dry the skin.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
Propan-2-ol (CAS 67-63-0)		
Aquatic		
<i>Acute</i>		
Crustacea	LC50	Daphnia magna > 10000 mg/l, 24 hours
Fish	LC50	Pimephales promelas 9640 mg/l, 96 hours
<i>Chronic</i>		
Crustacea	EC50	Daphnia magna > 100 mg/l, 21 days
	NOEC	Daphnia magna 141 mg/l, 16 days 30 mg/l, 21 days

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential Bioconcentration potential is low.

Partition coefficient n-octanol / water (log Kow)

Propan-2-ol (CAS 67-63-0) 0.05

Mobility in soil Isopropyl alcohol is highly mobile in soil.

Other adverse effects The product contains a volatile organic compound which has a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in accordance with all applicable regulations. Used wipes must be disposed in a closed container. Dispose of used wipes by dry waste to landfill.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport information

TDG

UN number UN3175
UN proper shipping name SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Isopropanol)
Transport hazard class(es)
Class 4.1
Subsidiary risk -
Packing group II
Environmental hazards No
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number UN3175
UN proper shipping name Solids containing flammable liquid, n.o.s. (Isopropanol)
Transport hazard class(es)
Class 4.1
Subsidiary risk -
Packing group II
Environmental hazards No.
ERG Code 3L
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN3175
UN proper shipping name SOLIDS CONTAINING FLAMMABLE LIQUID, N.O.S. (Isopropanol)
Transport hazard class(es)
Class 4.1
Subsidiary risk -
Packing group II
Environmental hazards
Marine pollutant No
EmS F-A, S-I
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

Canadian regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date	06-August-2021
Revision date	03-August-2022
Version No.	02
Further information	Further contact: Maclsaac & Associates 440 Gloucester Street, Suite 2111 Ottawa, Ontario, K1R 7T8 Canada +1 (613) 236-2250

Disclaimer Contec, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.